

36MM EXTRUDED

HIGH SECURITY COMMERCIAL ROLLER SHUTTER

HEAVY DUTY SHUTTER



WIDESPAN WIDTHS UP TO 5800MM

HEAVY DUTY DOUBLE WALL PROFILE

STRONG ALLOY CONSTRUCTION

COMMERCIAL GRADE PROTECTION FOR YOUR BUSINESS!

36MM EXTRUDED
EXTRUDED

36MM EXTRUDED ROLLER SHUTTERS

36mm Extruded Roller Shutters are ideal for heavy duty, high security commercial applications and are made with an aluminium precision extruded roller shutter profile. Suitable for many commercial and industrial grade applications, our **36mm Extruded Roller Shutters** provide high protection in a wide range of commercial applications such as shop fronts, factories and warehouses, restaurants, pharmacies, shopping mall entrances and sports complexes. **36mm Extruded Roller Shutters** are an ideal way to help keep your valuable business and premises protected.

Constructed with an extra strong and double wall extruded profile, **36mm Extruded Roller Shutters** provide heavy duty protection for window and door openings up to 5800mm wide.

At CW Shutters, we're committed to helping protect Australian businesses and their premises!



36MM EXTRUDED BENEFITS

- High quality, strong aluminium alloy construction.
- Commercial grade double wall extruded shutter profile for heavy duty strength.
- High quality powder coated finish.
- Double line grooved and slight curved face profile.
- Roll-tight design.
- Wide choice of profile colours.
- Heavy duty 68mm guide system for extra strength.
- Heavy duty steel axle and internal sealed bearings.
- Suitable for widespan widths up to 5800mm.
- Either manual or motorised operation.
- Made in Australia.

CONTROL OPTIONS



Steel Cable Winder
(Up To 50Kg)*



Spring Loaded
With Key Lock



SolarSmart™ Plus
Automation
With 12V Motor
(Up To 50Kg)*



PowerSmart™
Control System
With 12V Motor
(Up To 50Kg)*



Wall Switch
With 240V
Electric Motor*



Remote Control
With 240V Electric
SIMU Hz Motor*



Key Switch
With 240V
Electric Motor



Crank Handle
With 240V Electric
Manual Override
Motor



Key Ring Transmitter
With 240V Electric Motor &
SIMUDRIVE SD100 Hz Receiver & Control Unit*

* Control options must be installed in an indoor environment.

PROFILE COLOUR OPTIONS

Select from our wide range of high quality 36mm Extruded roller shutter profile colours.

	Cream		Black
	Magnolia Cream		Monument
	Clear Beige		Anodised Silver*
	White		Woodland Grey
	Shale Grey		

* Not available for pelmets & side frames.
Powder coated options available.

TECHNICAL SPECIFICATIONS

Maximum Shutter Width	5800mm (with Winged Slat Locks)
Maximum Shutter Height	3000mm
Profile Slat Covering	36mm
Profile Slat Thickness	9.7mm
Axle Types	Octagonal Steel
Bottom Bar Dimensions	55mm x 8.5mm
Guide Dimensions	68mm x 25mm/14mm (Heavy Duty Guide)
Paint Finish	High Quality Powder Coat

For more information on 36mm Extruded Roller Shutters, please contact your nearest dealer, installer or visit www.cwshutters.com.au!

Authorised Dealer:

**36MM EXTRUDED
EXTRUDED**



CW Shutters Manufactured By **CW Products** Tel: +61 8 8341 0120 Web: www.cwshutters.com.au

Illustrations, photos and colours shown in this brochure are for illustrative purposes only. All technical specifications and dimensions are correct at time of printing and may change without notice. For more information please contact your CW Shutters representative. 36mm Extruded and the 36mm Extruded logo are trademarks of CW Shutters. © 2024 CW Shutters.