50MM EXTRUDED VISION

PERFORATED VIEW COMMERCIAL ROLLER SHUTTER





50mm EXTRUDED VISION SHUTTERS

50mm Extruded Vision Roller Shutters are ideal for a wide range of commercial applications and are made with an aluminium precision extruded roller shutter profile, with approximately 20% vision and ventilation perforations. Suitable for many commercial and industrial grade applications, our 50mm Extruded Vision Roller Shutters provide protection in a wide range of commercial applications such as garage doors, shop fronts, factories and warehouses, restaurants, pharmacies and sports complexes.

50mm Extruded Vision Roller Shutters are an ideal way to help keep your business premises protected.

Constructed with a strong aluminium alloy and extruded profile, 50mm Extruded Vision Roller Shutters provide protection for openings up to 5500mm wide.

At CW Shutters, we're committed to helping protect Australian businesses and their premises!







50MM EXTRUDED VISION BENEFITS

- High quality, strong aluminium alloy construction.
- Commercial grade single wall extruded profile for heavy duty strength.
- Vision and ventilation perforations for airflow and light.
- High quality powder coated finish.
- Perforated and curved face profile.
- Roll-tight design.
- Choice of profile colours.
- Heavy duty steel axle and internal sealed bearings.
- Suitable for widespan widths up to 5500mm.
- Either manual or motorised operation.
- Made in Australia.

Authorised Dealer:

CONTROL OPTIONS







Spring Loaded With Key Lock



SolarSmart™ Plus Automation With 12V Motor (Up To 50Ka)



PowerSmart™ Control System With 12V Motor (Up To 50Ka)



With 240V Flectric Motor*



Remote Control With 240V Electric SIMU Hz Motor*



With 240V Electric Motor



With 240V Electric Manual Override



Control options must be installed in an indoor environment.

Key Ring Transmitter With 240V Electric Motor & SIMUDRIVE SD100 Hz Receiver & Control Unit*

PROFILE COLOUR OPTIONS

Select from our range of high quality 50mm Extruded Vision roller shutter profile colours.



Anodised Silver*

* Not available for pelmets & side frames. Powder coated options available.

TECHNICAL SPECIFICATIONS

Maximum Shutter Width	5500mm
Maximum Shutter Height	3000mm
Profile Slat Covering	50mm
Profile Slat Thickness	10.8mm
Axle Types	Octagonal Steel
Bottom Bar Dimensions	67mm x 10mm
Guide Dimensions	68mm x 25mm/18mm
Paint Finish	High Quality Powder Coat

For more information on 50mm Extruded Vision Roller Shutters, please contact your nearest dealer, installer or visit www.cwshutters.com.au!





