

IR50MM EXTRUDED

INTRUDER RESISTANT COMMERCIAL ROLLER SHUTTER

INTRUDER RESISTANT



HEAVY DUTY EXTRUDED PROFILE

WIDESPAN WIDTHS UP TO 7600MM

FLAT FACE ALLOWS FOR SIGNAGE

YOUR HIGHEST SECURITY COMMERCIAL SHUTTER SOLUTION!

IR50MM EXTRUDED

**INTRUDER
RESISTANT**

IR50mm EXTRUDED SHUTTERS

IR50mm (Intruder Resistant) Extruded Roller Shutters are ideal for high security applications and are made with an aluminium precision extruded roller shutter profile. Suitable for many high security commercial and industrial grade applications, our **IR50mm (Intruder Resistant) Extruded Roller Shutters** provide protection in a wide range of commercial applications such as garage doors, shop fronts, factories and warehouses, restaurants, pharmacies, sports complexes, scoreboards and high security areas.

Constructed with a strong aluminium alloy and extruded profile, **IR50mm (Intruder Resistant) Extruded Roller Shutters** provide protection for window, door and scoreboard openings up to 7600mm wide.

At CW Shutters, we're committed to helping protect Australian businesses and their premises!



IR50mm EXTRUDED BENEFITS

- High quality, strong aluminium alloy construction.
- Commercial grade double wall extruded profile for heavy duty strength.
- High quality powder coated finish or natural anodise.
- Flat face profile on both sides allows for sign writing.
- Choice of profile colours.
- Tubular motor or side motor (SIMUBOX) options.
- Single Phase and 3 Phase (High-Cycle) motor options.
- Safety Brakes are fitted as standard.
- 101.6mm x 2mm & 139.7mm x 3.5mm round steel axles.
- Suitable for widespan widths up to 7600mm (6100mm anodised).
- Motorised operation.
- Made in Australia.


* IR50mm Extruded Roller Shutters are not supplied with a pelmet. If a pelmet is required, you will need to fabricate your own solution.

CONTROL OPTIONS

Controller Options



SIMU Universal Key Switch



SIMU SD100 Hz Controller*



CWP S-30 Controller*



SIMU SD510 Controller*

Other Available Add-On Control Options




SIMU Key Ring Transmitter*



SIMU Hz Radio Key Pad*




SIMU Hz Dry Contact Transmitter*



SIMU 3 Button Wall Transmitter*



Key Ring Transmitter For S-30*



SIMU SA Hz Standard Receiver*

* Control options must be installed in an indoor environment.

If remote operation is required such as remote controls or connection to a building management system, a Safety Device is required such as Photo Safety Cells and/or Safety Edge.

Not all Add-On Control Options are compatible with all Controllers. Contact your dealer for more information.

PROFILE COLOUR OPTIONS

Select from our range of high quality IR50mm Extruded roller shutter profile colours.



TECHNICAL SPECIFICATIONS

Maximum Shutter Width	7600mm (6100mm Anodised)
Maximum Shutter Height	4500mm Drop + 500mm Head Room
Profile Slat Covering	50mm
Profile Slat Thickness	13mm
Axle Types	Round Steel
Bottom Foot Dimensions	75mm x 50mm
Guide Dimensions	82mm x 29mm/16mm (Heavy Duty Guide)
Paint Finish	High Quality Powder Coat

For more information on IR50mm Extruded Roller Shutters, please contact your nearest dealer, installer or visit www.cwshutters.com.au!

Authorised Dealer:

IR50MM EXTRUDED

**INTRUDER
RESISTANT**



CW SHUTTERS

CW Shutters Manufactured By **CW Products** Tel: +61 8 8341 0120 Web: www.cwshutters.com.au

Illustrations, photos and colours shown in this brochure are for illustrative purposes only. All technical specifications and dimensions are correct at time of printing and may change without notice. For more info please contact your CW Shutters representative. IR50mm (Intruder Resistant) Extruded and the IR50mm (Intruder Resistant) Extruded logo are trademarks of CW Shutters. © 2024 CW Shutters.